RAC Cabrillo Format

(Updated to conform for V3.0 update 2010 of Cabrillo standard) - See notes below.

START-OF-LOG: CREATED-BY: CALLSIGN: LOCATION:

CONTEST:

CATEGORY-OPERATOR:

CATEGORY-BAND: CATEGORY-MODE: CATEGORY-POWER:

CATEGORY-TRANSMITTER:

CLAIMED-SCORE:

CLUB: NAME: ADDRESS:

ADDRESS-CITY: ADDRESS-STATE-PROVINCE:

ADDRESS-POSTALCODE:

ADDRESS-COUNTRY:

EMAIL:

OPERATORS: SOAPBOX:

							info	sent			info rcvd-	
	freq	mo	da	te	time	call		rst	exch	call	rst	exch
0000	000001	1111	11111	122222	22222.	333333	33334444	14444	4455555	55555666	6666666777	7777778
1234567890123456789012345678901234567890123456789012345678901234567890												
QSO:	1825	CW	2003	-07-01	1044	VE3KZ		599	ON	VE4EAR	599	MB
QSO:	3510	CW	2003	-07-01	1044	VE3KZ		599	ON	K4BAI	599	103
QSO:	7155	PH	2003	-07-01	1044	VE3KZ		599	ON	K5MM	599	005
QSO:	14205	PH	2003	-07-01	1044	VE3KZ		599	ON	K4LTA	599	10
QSO:	21350	CW	2003	-07-01	1044	VE3KZ		599	ON	K1EA	599	55
QSO:	28375	PH	2003	-07-01	1050	VE3KZ		59	ON	VE5SF	59	SK
QSO:	50125	PH	2003	-07-01	1055	VE3KZ		59	ON	VE3EJ	59	ON
QSO:	146520	PH	2003	-07-01	1055	VE3KZ		59	ON	VE3CZ	59	ON

END-OF-LOG:

The RAC contest supports the use of 2 meters and 6 meters. In order to have the full 6 digits on 2 meters, you can use the normally reserved space between the : and start of frequency for the added character or drop the leftmost digit (1) from the frequency (e.g. instead of QSO:146520 write out QSO: 46520).

The log format above illustrates the layout of the RAC Cabrillo standard. There are several "tags" in the header plus QSO: tags in the main part of the log completed by an END-OF-LOG: tag. The four italic lines shown between SOAPBOX: and the first QSO: tag are there merely to indicate where the various columns of log data occur and what each column represents. **They do not appear in an actual Cabrillo log.**

<u>List of tags used in RAC Cabrillo.</u>

Please note, all tags should be in upper case characters.

START-OF-LOG: version-number

Must be the first line of the log submission. This structure is based on Cabrillo 3.0 and the RAC Cabrillo *version-number* should be 3.0.

END-OF-LOG:

Must be the last line of the log submission

CALLSIGN: callsign

The call sign used during the contest.

CATEGORY-BAND:

ALL, 160M, 80M, 40M, 20M, 15M, 10M, 6M, 2M

Must be one of the categories listed above

CATEGORY-MODE: SSB, CW, MIXED

Must be one of the modes listed above

CATEGORY-OPERATOR:

SINGLE-OP, MULTI-OP, CHECKLOG

Must be one of the options listed above

CATEGORY-POWER: HIGH, LOW, QRP

Must be one of the power levels listed above

CATEGORY-TRANSMITTER:

ONE, UNLIMITED

Must be one of the selections above

CLAIMED-SCORE: n

The claimed-score of the log submission, in integer form such as 12345.

CLUB: text

Name of the radio club with which the score should be aggregated (optional)

CONTEST: contest-name

The contest-name must be: RAC CANADA DAY or RAC CANADA WINTER

CREATED-BY: text

Name and version of the logging program used to create the Cabrillo file.

EMAIL: text

A place to put an email address, if desired

LOCATION: text

Canadian Province or Territory (RAC Section), US State or Territory, DXCC entity (Country) [for those outside CA or US] where the contest was operated from.

NAME: text ADDRESS: text ADDRESS-CITY: text

ADDRESS-STATE-PROVINCE: text ADDRESS-POSTALCODE: text ADDRESS-COUNTRY: text

Name and address of participant. A maximum of four ADDRESS: lines is permitted in addition to or instead of the extended ADDRESS elements (i.e. ADDRESS-CITY:)

OPERATORS: callsign1 [callsign2 callsign3...]

A space-delimited list of operator callsign(s). You may also list the callsign of the host station by placing an "@" character in front of the callsign within the operator list, such as

OPERATORS: @VE6RAC VE6JY VE6AO VE6DX

SOAPBOX: text

Soapbox comments, as many as neded.

QSO: qso-data

QSO data as specified by the RAC Cabrillo QSO data format.

List of tags NOT used in RAC Cabrillo format.

Please note, all tags should be in upper case characters.

These additional tags can be present and will be ignored by our log checking software.

CATEGORY-ASSISTED: CATEGORY-STATION: CATEGORY-TIME: CATEGORY-OVERLAY: OFFTIME: begin-time end-time

DEBUG: n

List of Column Abbreviations:

• freq:

For HF: integer frequency in kHz; if freq not known then 28000, 21000, 14000, 7000, 3500, 1800 For VHF/UHF; numeric band representations as follows: 50 MHz=50000, 144 MHz=144000 or 44000

• mo:

CW, PH, or FM

date:

UTC date in yyyy-mm-dd form

time:

UTC time in *nnnn* form

call: callsign

rst: RS(T)

• exch:

contest exchange